

WYKAZ STALI: Wylewki stropowe

Element	Nr pręta	Średn.	Gat.	Długość m	Ilość szt.	Długość łączna			
						A-0	A-III	A-III	A-III
						6	10	12	16
WYLEWKA STROP. Ws-1.1.	3	12	A-III	6,62	16			105,92	
	3'	12	A-III	6,62	16			105,92	
	4	12	A-III	3,72	8			29,76	
	4'	12	A-III	3,72	8			29,76	
	5	12	A-III	3,48	13			45,24	
	5'	12	A-III	3,48	13			45,24	
	6	12	A-III	3,55	8			28,40	
	6'	12	A-III	3,55	8			28,40	
WYLEWKA STROP. Ws-1.2.	3	12	A-III	5,03	16			80,48	
	3'	12	A-III	5,03	16			80,48	
	4	12	A-III	5,03	23			115,69	
	4'	12	A-III	5,03	23			115,69	
	5	12	A-III	2,03	12			24,36	
	5'	12	A-III	2,03	12			24,36	
	6	12	A-III	11,01	7			77,07	
	6'	12	A-III	11,01	7			77,07	
	7	12	A-III	8,51	15			127,65	
	7'	16	A-III	8,51	15				127,65
	8	16	A-III	2,50	4				10,00
	8'	12	A-III	2,50	4			10,00	
WYLEWKA STROP. Ws-1.3.	1	12	A-III	0,80	16			12,80	
	1'	12	A-III	0,80	16			12,80	
WYLEWKA STROP. Ws-2.1.	1	12	A-III	6,55	34			222,70	
	1'	12	A-III	6,55	34			222,70	
	2	12	A-III	6,47	33			213,51	
	2'	12	A-III	6,47	33			213,51	
	3'	12	A-III	2,25	20			45,00	
	4'	6	A-0	4,15	6	24,90			
	5	6	A-0	0,98	38	37,24			
	6	12	A-III	5,31	5			26,55	
	6'	12	A-III	5,31	4			21,24	
	7	12	A-III	1,38	134			184,92	
WYLEWKA STROP. Ws-2.2.	1	12	A-III	6,00	4			24,00	
	2	12	A-III	6,00	4			24,00	
	3	6	A-0	0,74	30	22,20			
	5	6	A-0	0,74	30	22,20			
	6	10	A-III	0,58	30		17,40		
WYLEWKA STROP. Ws-2.3.	3	12	A-III	6,37	33			210,21	
	3'	12	A-III	6,37	33			210,21	
	4	12	A-III	1,90	8			15,20	
	4'	12	A-III	1,90	8			15,20	
	5	12	A-III	2,41	8			19,28	
	5'	12	A-III	2,41	8			19,28	
	6	16	A-III	3,20	8				25,60
	6'	16	A-III	3,20	8				25,60
	7	12	A-III	8,31	20			166,20	
	7'	12	A-III	8,31	20			166,20	
	8	12	A-III	1,25	10			12,50	
	8'	12	A-III	1,25	10			12,50	
	9	12	A-III	5,50	10			55,00	
	9'	12	A-III	5,50	10			55,00	
	10	12	A-III	2,70	8			21,60	
	10'	12	A-III	2,70	8			21,60	
	11	12	A-III	1,00	8			8,00	
	11'	12	A-III	1,00	8			8,00	
	12	12	A-III	1,38	177			244,26	

WYLEWKA STROP. Ws-2.4.	1	12	A-III	6,00	14			84,00	
	2	6	A-0	1,88	60	112,80			
	3	12	A-III	0,51	3			1,53	
	4	12	A-III	0,63	3			1,89	
	5	10	A-III	1,44	26		37,44		
WYLEWKA STROP. Ws-2.5.	1	12	A-III	5,25	9			47,25	
	1'	12	A-III	5,25	9			47,25	
	2	12	A-III	0,98	2			1,96	
	2'	12	A-III	0,98	2			1,96	
	3	12	A-III	2,21	2			4,42	
	3'	12	A-III	2,21	2			4,42	
	4	12	A-III	4,25	2			8,50	
	4'	12	A-III	4,25	2			8,50	
	5	12	A-III	2,95	16			47,20	
	5'	12	A-III	2,95	16			47,20	
	6	12	A-III	1,22	10			12,20	
	7	12	A-III	1,52	5			7,60	
	7'	12	A-III	1,52	5			7,60	
	8	12	A-III	1,22	10			12,20	
	9	12	A-III	2,01	5			10,05	
	9'	12	A-III	2,01	5			10,05	
	10	12	A-III	1,38	80			110,40	
	11	12	A-III	2,90	9			26,10	
	12	6	A-0	0,98	10	9,80			
WYLEWKA STROP. Ws-2.6.	1	12	A-III	4,80	12			57,60	
	2	6	A-0	0,80	3	2,40			
	3	6	A-0	1,88	45	84,60			
WYLEWKA STROP. Ws-2.7.	1	12	A-III	3,90	14			54,60	
	2	6	A-0	1,20	38	45,60			
	3	12	A-III	1,48	19			28,12	
WYLEWKA STROP. Ws-2.8.	3	12	A-III	1,60	14			22,40	
	3'	12	A-III	1,60	14			22,40	
	4	12	A-III	3,20	6			19,20	
	4'	12	A-III	3,20	6			19,20	
	8	12	A-III	1,38	40			55,20	
WYLEWKA STROP. Ws-2.9.	1	12	A-III	2,70	14			37,80	
	1'	12	A-III	2,70	14			37,80	
	2	12	A-III	3,20	12			38,40	
	2'	12	A-III	3,20	12			38,40	
	8	12	A-III	1,38	72			99,36	
Razem długość				[m]		361,74	54,84	4668,22	188,85
Ciężar jednostkowy				[kG/m]		0,222	0,617	0,888	1,578
Ciężar				[kG]		80,31	33,84	4145,38	298,01
Ciężar ogółem gatunkami				[kG]		80,31	4477,22		