

Product Specification

NW2

Outdoor Unit

Model Name					AM200AXVGGH/EU
Module					Single
Power Supply				Ø, #, V, Hz	3 4 380-415 50
Mode					HP
Performance	HP				20
	Capacity	Cooling	Rated	kW	56.00
		Heating	Rated	kW	56.00
			Max	kW	63.00
Power	Power Input	Cooling	Rated	kW	24.89
		Heating	Rated	kW	16.57
	Current Input	Cooling	Rated	A	38.63
		Heating	Rated	A	25.72
	Current	MCA		A	43.00
		MFA		A	63.00
Casing	Material	Body			GI Steel Plate
		Base			GI Steel Plate
Heat Exchanger	Type				Fin & Tube
	Material	Fin			Al
		Tube			Cu
	Fin Treatment				Anti-corrosion
Compressor	Quantity			EA	1
Fan	Type				Propeller
	Discharge direction				Top discharge
	Air Flow Rate	High		CMM	313
	External Static Pressure	Max		Pa	107.87
Fan Motor	Type				BLDC
	Quantity			EA	2
	Output			W	620
Piping Connections	Liquid Pipe	Type			Welding
		Diameter		mm	15.88
	Gas Pipe	Type			Welding
		Diameter		mm	28.58
Wiring connections	Communication	Min.		mm²	0.75
		Comm.Layer			F1, F2
Refrigerant	Type				R410A

Product Specification

NW2 (Continued)
Outdoor Unit

Refrigerant	Factory Charging		kg	10.50
	CO2 emission		tCO2e	21.92
Sound	Sound	Cooling	dB(A)	61
	Pressure			
	Sound	Cooling	dB(A)	84
External Dimension	Power Level			
	Net Weight		kg	268.00
	Shipping Weight		kg	285.00
	Net Dimensions	W	mm	1295
		H	mm	1695
		D	mm	765
	Shipping Dimensions	W	mm	1363
		H	mm	1887
		D	mm	829
Operating Temp. Range	Cooling	Min.	°C	-5.0
		Max.	°C	50.0
	Heating	Min.	°C	-25.0
		Max.	°C	24.0